



FTP Solid Cable

Box of 305 meters

Description


Extended frequency to 100MHz
 4 x 24 AWG – FTP PVC Cable
 Backward-compatibility with all CAT.5
 Products and application
 Guarantee full-duplex and crosstalk
 values
 RoHS compliant
 Solid bare copper conductors
 insulated with thermoplastics
 polyolefin

QP - 65704A

Category 5E, FTP Solid Cable, 24 AWG

Specifications

Cable type	4 pairs FTP
Conductor AWG Stranded	24 AWG
Diameter	0.51 ± 0.01mm
Insulation Type	PE 1.03 ± 0.05mm
Jacket Type	PVC 5.99 ± 0.3mm
Packing m	Rb305
Jacket available	PVC
Color	Grey
Electrical Performance	100 meters Cable Data
Characteristic Impedance	(1-100MHz): 100 ± 15 %?
Pair-to-ground capacitances unbalance (pF/km) Max.	1600
Propagation Delay (ns/100m) Max.	534 + 36 / vf
Conductor resistance (Ohm/100m@20)	9.5





FTP Solid Cable

Box of 305 meters

Features

Standards

International: IEC 61156-5 edit. 2.0

North American: ANSI/TIA/EIA-

568-B. 2-1 Cat5e

UL Listed E222843 verified

QP - 65704A

Category 5E, FTP Solid Cable, 24 AWG

Technical Data

IEC 61156-5 ed2.0 Category 5e horizontal cable parameters							
Freq. (MHz)	Ins. Loss (dB/100m)	RL (dB)	Pair to Pair		Power Sum		Po. Delay (n/s 100)
			NEXT	ELFLEX	NEXT	ELFLEX	
			(dB/100)		(dB/100)		
	Máx.	Mín.	Mín.	Mín.	Mín.	Mín.	Máx.
1	--	20.0	--	--	--	--	--
4	4.1	23.0	56.3	52.0	53.3	55.0	552.0
10	6.5	25.0	50.3	44.0	47.3	47.0	545.4
16	8.3	25.0	47.2	39.9	44.2	42.9	543.0
20	9.3	25.0	45.8	38.0	42.8	41.0	542.0
31.25	11.7	23.6	42.9	34.1	39.9	37.1	540.4
62.5	17.0	21.5	38.4	28.1	35.4	31.1	538.6
100	22.0	20.1	35.3	24.0	32.3	27.0	537.6